

Design S8636 A/B • Hat and Loop with Lace Pattern

Hat: to fit 20½"-22" [52-56cm] head.

Loop: about 8⅝" [22cm] wide and 59" [150cm] in circumference.

Materials: Schachenmayr original Northern, 1 ball [100g] for the hat and 3 balls [300g] for the loop each #00220 teal.

One each US 6-8 [4-5mm] and US 7-9 [4.5-5.5mm] circular needle 16" [40cm] long, plus five US 7-9 [4.5-5.5mm] dpn for the hat, five US 7 [4.5mm] needles for the loop, and one cable needle for both designs.

Rib pattern: alt K1, P1.

Basic pattern: work foll chart in rnds for hat, and in rows for loop. All rnds or rows are shown as sts appear on RS of work. Read rnds and RS rows from right to left, and WS rows from left to right.

Hat: work rnds 1 and 2 once, then rep rnds 3 to 14 throughout.

Loop: rep rows 3 to 14 throughout.

3 selvage sts for the loop: at each end work in RS rows K1, then sl1p wyif, K1; in WS rows sl1p wyif, K1, slip wyif.

Gauge: with 4.5-5.5mm needles and basic pattern (stretched slightly) 20 sts and 24 rnds/rows, each to 4" [10cm].

INSTRUCTIONS, Hat

With 4-5mm circular needle cast on 80 sts and work 2" [5cm] rib patt; start rnd with P1.

Cont with 4.5-5.5mm needles and basic patt = motif of 16 or 20 sts 5 times. After 1st rnd there are 100 sts on the needle.

When work measures 8⅝" [22.5cm], after a 6th rnd patt, start to dec as foll (change to the dpn as required): P the 3 P sts tog 10 times = 80 sts. Cont with st-st.

In 2nd foll rnd K2tog every 2 sts 26 times, end with K2 = 54 sts.

In 2nd foll rnd K2tog every 2 sts 18 times = 36 sts.

In 2nd foll rnd K2tog every 2 sts 12 times = 24 sts.

Then K2tog throughout until 6 sts rem. Pull sts tog firmly with the remaining yarn and darn away yarn tail.

Total height about 10¼" [26cm].



INSTRUCTIONS, Loop

Cast on 59 sts and work 1st WS row as foll: 3 selvage sts, ★K3, P3, K1, P3, rep 4 times from ★, K3, 3 selvage sts. Cont with basic patt as foll: 3 selvage sts, motif of 20 sts 2 times, sts 1 to 13 of motif once, 3 selvage sts.

In height work rows 3 to 14 30 times, binding off sts in last row.

Finishing: block piece to measurements, cover with a damp cloth and allow to dry. Sew cast-on and bound-off edges tog.

